R2416ULCB
AC Rack Mount CCTV Power Supply

Rev. DSR2416ULCB_09272011

R2416ULCB

Overview

This Altronix AC Rack Mount CCTV Power Supply provides 24VAC or 28VAC distributed via sixteen (16) PTC protected Class 2 Rated power limited outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:
- 115VAC, 50/60Hz, 3 amp.

Output:
- Sixteen (16) PTC protected Class 2 Rated power limited outputs.
- 24VAC @ 7 amp (168VA) or 28VAC @ 6 amp (168VA) supply current.
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Visual Indicators:
- Individual power LED indicators.

Features:
- Illuminated power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.

Features *(cont'd)*:
- Removable terminal blocks with locking screw flange.
- Spare fuses provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- 2U rack mount chassis for use in standard EIA 19" rack.
- Operating temperature: 0º C to 49º C ambient.
- Total system power consumption: 175 W.
- BTU/Hr.:
  - 24VAC: 73 BTU/Hr.
  - 28VAC: 74 BTU/Hr.
- System AC input VA requirement: 175 VA.
- Product weight (approx.): 16.15 lbs. (7.33 kg.)
- Shipping weight (approx.): 17.15 lbs. (7.78 kg.)

Agency Approvals

UL Listed for Commercial CCTV Equipment (UL 2044).

CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

European Conformity

Enclosure Dimensions *(H x W x D) (approximate)*:

3.26” (83mm) x 19.125” (486mm) x 8.5” (216mm)